

# HID® ADR100

## ID-1 Photo ID Scanner



### STATE-OF-THE-ART

The ADR100 Photo ID Scanner (ID-1 size) captures high-quality full-color and ultraviolet (UV) images of ID cards. Designed for dependable performance in both indoor and outdoor environments, it ensures accurate image capture regardless of lighting or weather conditions.

### AUTOMATICALLY DETECTED, CROPPED AND ROTATED

When a credit card sized photo ID is presented to the scanner the photograph on the card is automatically detected, cropped and rotated, allowing both the holder's portrait and card images to be displayed right-way-up.

### SUPPORTED DOCUMENTS

ID-1 (credit card) sized documents supported by the ADR100 include:

- All US federal and state issued ID cards, such as driver's licenses, photo IDs, voter IDs, social security cards, medical ID cards, immigration IDs and resident permits
- All North American, European and other national driving licenses
- All European and other national ID and e-ID cards
- EHIC (European Health Insurance Card)

### APPLICATIONS


- Integration into self-service kiosks
- Customer identity verification, including age and anti-money laundering identity checks
- Virtual teller machines, virtual ticket offices



### FEATURES:

- **Full-Page Capture** - Documents imaged in color and UV
- **Documents Read** - ID cards, driving licenses and resident permits
- **Barcode Reading** - Option to also read 1D and 2D barcodes
- **Indoor and Outdoor** - Designed for use in all environments
- **Intuitive Use** - Audio beep to confirm successful data capture
- **Frontline Use** - Robust, compact and maintenance-free design
- **Replaceable Glass** - Replaceable toughened and scratch-resistant 4mm glass face

# ADR100



## FEATURES

### Connection Types

• USB

### Image Capture

• Visible

• Ultraviolet\*

### Technology

• QR/Barcode\*

### Reader Size

• Full Page

\* Option

[Learn more >>](#)

[Contact sales >>](#)

## ADR100

|                                 | READING CAPABILITIES                                                                                                                                       |
|---------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Imaging</b>                  | Full-page: JPG, BMP, TIFF, PNG<br>Illumination sources: visible/white, UV LED's *<br>Resolution: 600 DPI                                                   |
| <b>Barcode Reading (Option)</b> | Linear (1D): EAN / UPC, Code 2 of 5, Interleaved 2 of 5, IATA 2 of 5, Code 39, Code 128<br>2D: IATA resolution 792, PDF417, Aztec, DataMatrix and QR codes |
|                                 | <b>ELECTRONIC</b>                                                                                                                                          |
| <b>Power Supply</b>             | +24 VDC PSU via Molex connector                                                                                                                            |
| <b>Communication</b>            | USB 2.0                                                                                                                                                    |
| <b>Connection</b>               | Micro AB USB connector                                                                                                                                     |
| <b>Host Minimum</b>             | Windows 7 & above, 32/64 bit; Pentium Core-i3 2.1GHz & 4GB RAM                                                                                             |
| <b>Host Recommended</b>         | Win 7 & above, 32/64 bit; Pentium Core-i5 3.3GHz & 8GB RAM                                                                                                 |
|                                 | <b>PHYSICAL</b>                                                                                                                                            |
| <b>Dimensions</b>               | 4 x 3 x 3 in<br>(106 x 86 x 79 mm)                                                                                                                         |
| <b>Body</b>                     | Black ABS                                                                                                                                                  |
| <b>Glass</b>                    | 4mm Toughened Platen BS EN60068-2-75 & IEC 62262:2002, rated to 6.375J impact, with AR coating<br>Scratch-resistant coating options are available          |
| <b>Weight</b>                   | 10 oz. (285g) excl. cable/PSU                                                                                                                              |
|                                 | <b>THERMAL (AIR)</b>                                                                                                                                       |
| <b>Temperature</b>              | Operating 32°F to 122°F ( 0°C to 50°C)                                                                                                                     |
| <b>Storage</b>                  | 32°F to 140°F (0°C to 60°C)                                                                                                                                |
| <b>Humidity</b>                 | 0-95% non-condensing                                                                                                                                       |
|                                 | *WARNING – The quality of a UV image can be adversely affected in high brightness conditions due to sunlight being transmitted through a scanned document. |

**HID**

hidglobal.com

North America: +1 512 776 9000 | Toll Free: 1 800 237 7769

Europe, Middle East, Africa: +353 91 506 900

Asia Pacific: +852 3160 9800 | Latin America: +52 55 9171 1108

**For more global phone numbers click here**

© 2025 HID Global Corporation/ASSA ABLOY AB. All rights reserved.

2025-09-30-bio-adr100-id-scanner-ds-en PLT-06252

Part of ASSA ABLOY