

LinTRAK C10SMRI-M850

HID's LinTRAK® ultra-high frequency RAIN® (UHF) radio-frequency identification (RFID) tags have been specifically designed to identify textile products; thanks to their shape, durability, and ease of fixation, they meet the tracking requirements of the laundry industry.

They withstand the rigors of repeated washings, including exposure to water, cleaning chemicals, sterilizing heat, and water extraction pressure. The patented process securely positions the inner chip relative to the antenna, which guarantees consistent performance over the life of the tag.

LinTRAK tags are compliant with EPC global UHF Class 1 Gen 2 and ISO 1800-63 RAIN® RFID standards. This means that they are encoded with a unique EPC code following GS1 standards (SGTIN96 format), which can be re-programmed to be compatible with any operating platform in accordance with privacy laws. Custom encoding services are provided.

MR conditional tags are undetectable by needle detector machines and validated by the world's most experienced MR-safety testing company (MRSTS) at 1.5 and 3.0 Tesla, which is the highest rating that can be applied for an RFID device. This means that a patient with this device (integrated to linen or gown) can be scanned safely in an MR system.

LinTRAK C10S-MRI-M850 features a soft and flexible design, ideal for integration into textile products. Measuring just 10 x 52 mm, LinTRAK C10S-MRI-M850's low footprint allows for a more discreet insertion into fine linen items and garments, either sewn in a hem or fixed under a heatseal label.

LinTRAK C10S-MRI-M850 embeds the latest generation IC from IMPINJ implementing GEN2X for enhanced performance and increased security, making this RFID tag an optimal choice for demanding textile services applications.



UHF TAGS FOR TEXTILE SERVICES:

- 10 x 52 mm
- Specifically designed to identify textile products
- Resistant to harsh laundry processes
- Small, discreet and easy to integrate
- MR-conditional RFID tag for use in medical environments
- Utilizes the latest generation IC from IMPINJ implementing GEN2X for enhanced performance, increased security

KEY TECHNOLOGY HIGHLIGHTS:

- . UHF: RAIN EPC Class 1 Gen 2 and ISO 18000-63
- . Water, chemical, heat and mechanical pressure resistance
- . Guaranteed to withstand 200 commercial washing cycles or three years
- . OEKO-TEX® STANDARD 100 Level 1 certified

LinTRAK C10S-MRI-M850



Base Model Number	TL850E04
	ELECTRONIC
Operating Frequency	860-960 MHz (worldwide)
Chip Type	Impinj M850
Memory	96 bits EPC / 32 bits User
Reading distance (2W reader ERP, free space)	Up to 16 ft (5 m)
	PHYSICAL
Dimensions (Length +/- 2 mm Height +/- 1 mm)	0.4 x 2.04 in (10 x 52 mm)
Thickness	0.078 in (2 mm) on chip location only, rest of tag is <0.008 in (0.2 mm)
Mounting Method	Sewn, inserted inside hem or pouch, or fixed under a heat-seal label
Material	UHF module: encapsulated chip, epoxy Antenna: stainless steel multithreads Fabric label: polyester and polyurethane as external layer
Color	White
	WASHING
Max Temperature	428°F (220°C) / 30 seconds
Exposure	2,5 bars (36,25 PSI)
Tunnel Washer	194°F (90°C) / 15 minutes
Pre-Drying in Tumbler	320° F (160° C) / 30 minutes
Tunnel Finisher	365° F (185° C) / 30 minutes
Sterilization Process	273°F (134°C) / 2 bars / 10 minutes
Water Extractor Press	60 bars (performance level measured and guaranteed in HID's laundry tests and conditions)
Chemical Resistance	All standard chemicals used in laundry process
	OTHER
Standards	UHF EPC Class 1 Gen 2, ISO 18000-63
Certifications	OEKO-TEX® STANDARD 100 Level 1 MR-Conditional
Box Size	Bags of 200 pcs in boxes of 10000 pcs
Personalization	Unique EPC code (unlocked). Custom encoding possible. Can be laser-marked with TID.
Waranty	200 washing cycles (according to ISO 15797:2017) or 3 years



hidglobal.com

North America: +1 512 776 9000 | Toll Free: 1 800 237 7769
Europe, Middle East, Africa: +353 91 506 900
Asia Pacific: +852 3160 9800 | Latin America: +52 55 9171 1108
For more global phone numbers click here

© 2026 HID Global Corporation/ASSA ABLOY AB. All rights reserved.
2026-02-25-idt-ts-lintrak-c10s-mri-m850-ds-en
Part of ASSA ABLOY

For more information, contact: tagsales@hidglobal.com