

RP9000 BGR Printer

For Check-in and Boarding Gates



SIMPLE AND RELIABLE RECEIPT PRINTING

The RP9000 boarding gate receipt printer provides a simple and reliable means to print receipts at airport check-in and boarding gates. It can be used to facilitate seat assignment for passengers boarding with 2D barcoded boarding passes on home-printed documents or electronic media. In addition, it can be used to offer frequent flyer points receipts. As a plug-and-play accessory to the HID Global's range of boarding gate readers, the RP9000 is simple to deploy.

LOW-COST CHECK-IN PRINTER

The RP9000 printer, via its USB interface, can also be employed as a low-cost check-in printer. Using a supplied USB driver, boarding passes can be easily printed using Windows' spooler mechanism.

MAXIMIZES THROUGHPUT

The compact design incorporates a large 90mm diameter paper roll, providing 92 meters of paper which minimizes operational disruption caused by roll changes.

ACCESSORIES

The quick release bracket for the RP9000 BGR printer provides a simple means to secure the printer to counter-tops or podiums, preventing it from being damaged or stolen and acting as a simple but effective deterrent to agents relocating the hardware.

APPLICATIONS


- Printing boarding passes at check-in desk
- Seat assignment for passengers with electronic or home-printed documents
- Seat assignment changes at the gate
- Frequent flyer points receipts



FEATURES:

- Passenger Experience - Simplifies passenger boarding saving time
- Big Capacity - 92-meter paper roll capacity with greater than 1100 passengers between changes
- Easy Operation - Compact and rugged design with fast, quiet operation
- Simple Integration - 'Plug and play' with HID Global's boarding gate reader
- Saves Time - Eliminates 'cutting and sorting'

RP9000 BGR Printer



FEATURES

Connection Types

 RS232

RP9000 BGR Printer

	PRINTING
Specification	Printing method: Thermal line printing Resolution: 203 DPI Printing speed: 220mm/s Paper width: 80mm or 82.5mm Roll dimension: Up to 90mm diameter with 92 metre standard length roll
	ELECTRONIC
Power Supply	Supplied with external universal AC power supply, 100-240V, 50/60Hz
Interface	RS232 to match printer port of Access-IS BGR range of devices
	PHYSICAL
Dimensions	6 x 8 x 6 in (140 x 208 x 152 mm)
Weight	4 lbs. (2000g)
Colour	Grey
MTBF	360,000 hours
	THERMAL (AIR)
Temperature	Operating 32°F to 122°F (0°C to 50°C)
Storage	32°F to 140°F (0°C to 60°C)
Humidity	0-95% non-condensing
	APPROVALS
	Safety approvals: EN60950 Agency approvals: CE, UL, TUV



hidglobal.com

North America: +1 512 776 9000 | Toll Free: 1 800 237 7769
Europe, Middle East, Africa: +44 1440 714 850
Asia Pacific: +852 3160 9800 | Latin America: +52 (55) 9171-1108
For more global phone numbers click here

© 2021 HID Global Corporation/ASSA ABLOY AB. All rights reserved.
2021-10-27-bio-rp9000-printer-ds-en PLT-06281
Part of ASSA ABLOY