



Supported HID Fingerprint Readers

				
TECHNOLOGY	Optical	Capacitive (FAP 10 PIV)	Capacitive (STQC)	Multispectral (Lumidigm™)
Product Family	DP4500 (coated & uncoated)	EikonTouch TC710 (Gold Coat)	EikonTouch TC510 (SteelCoat)	V311
SKU	50012-001-104 (Most common SKU. Other variants available)	TC710-A3-01 (Most common SKU. Other variants available)	TC510-A3-01 (Most common SKU. Other variants available)	M311-00-01
Biometric Processing	On Host (Streaming)	On Device or On Host (Secure channel option)	On Device or On Host (Secure channel option)	On Host (Streaming)
Capture Area	15.24 x 17.78mm ellipse (0.6 x 0.7 inch)	12.8 x 18mm (0.5 x 0.7 inch)	12.8 x 18mm (0.5 x 0.7 inch)	18 x 28mm ellipse (0.7 x 1.1 inch)
Ingress Protection (Dust/Water)	—	IP65	IP65	IP65
Liveness (Presentation Attack Detection)	Limited	Good (ISO 30107-3 level-1)	Good (ISO 30107-3 level-1)	Strong (ISO 30107-3 level-1)
Operating Systems	Dell Wyse ThinOS 9.1+, DigitalPersona Biometric SDK 3.4+ for Windows 7/8/10 DigitalPersona Biometric SDK 3.2+ for Linux & Android			Lumidigm SDK 8: Windows 7/8.1/10, Linux PC 32/64, Linux Embedded ARM V7/8, DigitalPersona Biometric SDK 3.4+

COMPARISON CHART



hidglobal.com

North America: +1 512 776 9000 | Toll Free: 1 800 237 7769
Europe, Middle East, Africa: +44 1440 714 850
Asia Pacific: +852 3160 9800 | Latin America: +52 (55) 9171-1108
For more global phone numbers click [here](#)

© 2022 HID Global Corporation/ASSA ABLOY AB. All rights reserved.
2021-09-14-bio-supported-hid-fingerprint-readers-cc-en PLT-06155
Part of ASSA ABLOY

